


SUS 304●/304L●/316●/310S●/347■/4571▲ TP-S

呼び径		外径	Sch5S		Sch10S		Sch20S		Sch40S		Sch80S		Sch120		Sch160		XXS	
A	B																	
6	1/8	10.5	1.0	●	1.2	●	1.5	●	1.7	●	2.4	●	—	—	—	—	—	—
8	1/4	13.8	1.2	●	1.65	●	2.0	●	2.2	●	3.0	●	—	—	—	—	—	—
10	3/8	17.3	1.2	●	1.65	●	2.0	●	2.3	●	3.2	●	—	—	—	—	—	—
15	1/2	21.7	1.65	●■	2.1	●■	2.5	●■	2.8	●■	3.7	●■	—	—	4.7	●■	7.5	●
20	3/4	27.2	1.65	●■	2.1	●■	2.5	●■	2.9	●■	3.9	●■	—	—	5.5	●■	—	—
25	1	34	1.65	●▲	2.8	●▲	3.0	●▲	3.4	●▲	4.5	●▲	—	—	6.4	●▲	—	—
32	1-1/4	42.7	1.65	●	2.8	●	3.0	●	3.6	●	4.9	●	—	—	6.4	●	—	—
40	1-1/2	48.6	1.65	●■	2.8	●■	3.0	●■	3.7	●■	5.1	●■	—	—	7.1	●■	—	—
50	2	60.5	1.65	●■	2.8	●■	3.5	●■	3.9	●■	5.5	●■	—	—	8.7	●■	—	—
65	2-1/2	76.3	2.1	●	3.0	●	3.5	●	5.2	●	7.0	●	—	—	9.5	●	—	—
80	3	89.1	2.1	●	3.0	●	4.0	●	5.5	●	7.6	●	—	—	11.1	●	—	—
90	3-1/2	101.6	2.1	●	3.0	●	4.0	●	5.7	●	8.1	●	—	—	12.7	●	—	—
100	4	114.3	2.1	●	3.0	●	4.0	●	6.0	●	8.6	●	11.1	●	13.5	●	—	—
125	5	139.8	2.8	●■	3.4	●■	5.0	●■	6.6	●■	9.5	●■	12.7	●■	15.9	●■	—	—
150	6	165.2	2.8	●▲■	3.4	●▲■	5.0	●▲■	7.1	●▲■	11.0	●▲■	14.3	●▲■	18.2	●▲■	—	—
200	8	216.3	2.8	●▲	4.0	●▲	6.5	●▲	8.2	●▲	12.7	●▲	18.2	●▲	23.0	●▲	—	—
250	10	267.4	3.4	●▲	4.0	●▲	6.5	●▲	9.3	●▲	15.1	●▲	21.4	●▲	28.6	●▲	—	—
300	12	318.5	4.0	●■	4.5	●■	6.5	●■	10.3	●■	17.4	●■	25.4	●■	33.3	●■	—	—
350	14	355.6	5.0	●	6.4	●	7.9	●	11.1	●	19.0	●	27.8	●	35.7	●	—	—
400	16	406.4	—	—	—	—	—	—	12.7	●	21.4	●	30.9	●	40.5	●	—	—



We build the legend by stainless steel.