

SUS304 (熱間圧延品・溶接品)・316・316L チャンネル (溶接品) 定尺4,000・6,000mm・単位：mm

サ イ ズ t×B×H	kg/P			r ₁	r ₂
	SUS304		SUS316L		
	4,000	6,000	6,000		
3× 20× 40		10.8		4	2
3× 25× 50		13.7		4	2
○ 3× 40× 80		22.3		4.5	2
○ 3× 50×100		28.5		6.5	2
4× 50×100	24.8	37.2	37.4	6.5	3
5× 40× 80	24.0	35.9	36.1	4.5	3
5× 50×100	30.6	45.9	46.2	6.5	3
6× 50×100	36.1	54.1	54.4	6.5	4.5
○ 6× 60×120		65.4		6.5	4
6× 65×130	48.0	72.0	72.6	8.5	4
6× 75×150	55.6	83.4	84.0	8.5	4
○ 6×100×200	74.8	112.0		10	5
○ 8×100×200	98.4	148.0		10	6
9× 75×150	81.2	122.0	122.0	8.5	6
※ 10×100×200	121.0	182.0	183.0	10	7

断面 積(a) (cm ²)	重心の位置 (cm)		断面二次モーメント(i) (cm ⁴)		断面二次半径 (i) (cm)		断面係数(Z) (cm ³)	
	C _x	C _y	I _x	I _y	i _x	i _y	Z _x	Z _y
2.271	0	0.59	5.22	0.778	1.52	0.585	2.61	0.552
2.871	0	0.72	10.6	1.60	1.92	0.746	4.26	0.895
4.690	0	1.09	46.6	7.07	3.15	1.23	11.7	2.43
5.990	0	1.32	94.7	14.2	3.98	1.54	18.9	3.86
7.823	0	1.36	121.0	18.2	3.93	1.52	24.2	4.99
7.548	0	1.16	71.1	10.9	3.07	1.20	17.8	3.83
9.643	0	1.40	146.0	22.1	3.89	1.52	29.2	6.16
11.37	0	1.43	168.0	25.3	3.85	1.49	33.7	7.09
13.79	0	1.69	300.0	45.6	4.66	1.82	50.0	10.6
15.12	0	1.80	390.0	58.9	5.08	1.97	60.0	12.5
17.52	0	2.05	609.0	92.3	5.89	2.30	81.2	16.9
23.60	0	2.65	1490.0	225.0	7.94	3.09	149.0	30.6
31.00	0	2.73	1910.0	290.0	7.85	3.06	191.0	39.9
25.54	0	2.16	850.0	129.0	5.77	2.25	113.0	24.2
38.22	0	2.81	2310.0	351.0	7.77	3.03	231.0	48.8

○…溶接品 ※…6M圧延品、4M溶接品 ※重量を表示しているサイズは即納品です。

